

D

D

C

C

B

B


A

A

| Main Specification | | | |
|-----------------------|-----------|------------|------------|
| Magnification | 0.9X | 10X | 11X |
| Working Distance | 176.7±5 | 164.2±5 | 153.7±5 |
| Image Distance | 144.8±2.5 | 156.11±2.5 | 167.67±2.5 |
| Conjugate Distance | 401.8±9 | 400.56±9 | 401.67±9 |
| Flange Focal Distance | 175.4 | 186.7 | 198.3 |
| Max image | φ62 | | |
| F/# | 4.5 | | |
| EFL | 116 | | |
| FOV | 28° | | |
| ENP Diameter | 25.6 | | |
| Distortion | <0.05% | | |
| IMAGE QUALITY | | | |
| AXIS | φ46.2 | φ66 | |
| | | | |

| | |
|-------------------------|---------|
| Image space NA | 0.062 |
| Object space NA | 0.062 |
| Entrance pupil diameter | 25.63 |
| Entrance pupil position | 38.63 |
| Exit pupil diameter | 30.93 |
| Exit pupil position | -24.965 |

注：
Logo上的圆点粘贴位置与成像面垂直为最佳成像点。

| | | | | | | | |
|--|-----|------------|----|---|-----|-----|--|
| TOLERANCE: LINEARITY TOLERANCES +0.05 ANGULAR TOLERANCES ARE±30° DRAFT ANGLES ARE±0.9°/SIDE | | | |  | | 三角法 | |
| 材料(环保) | | | | 单位 | | 比例 | |
| LS1210A技术规格图 | | | | mm | | 1:1 | |
| 设计 | 朱周德 | 2017-03-30 | 名称 | | 页码 | | |
| 校对 | | | | | 1/1 | | |
| 审核 | | | | | 版本 | | |
| 批准 | | | 代号 | | V1 | | |