



注:

LOGO上的圆点粘贴位置与成像面垂直为最佳成像点。

Main Specification				Image space NA		0.045
Magnification	1.45X	1.7X	2X	Object space NA		0.076
Working Distance(A+B)	167.2±5	148.83±5	135.7±5	Entrance pupil diameter		33.3
Conjugate Distance	586.5±9	611.85±9	643.1±9	Entrance pupil position		62.1
Flange Focal Distance	337.86±0.5	381.66±0.5	425.6±0.5	Exit pupil diameter		36.8
Max image circle	φ82			Exit pupil position		-4.09
F/#	3.8-16					
EFL	116					
Distortion	0.007%					
Structure	8G					
IMAGE QUALITY						
AXIS	φ16.2	φ66	φ82	Z1	Z2	Z3
200lp/mm	100lp/mm	80lp/mm	80lp/mm	标记	处数	更改文件号
						担当
						变更日期

TOLERANCE:		LINEARITY TOLERANCES: +0.05		ANGULAR TOLERANCES ARE ±30°	
DRAFT ANGLES ARE 1:5 SIDE		三角法		材料(环保)	
设计		校对		单位	
2019.9.6		2019.9.6		比例	
名称		规格书		页码	
代号		LS1617L-P01-SPEC		1/1	
批准		变更日期		版本	
林金全		2019.9.6		V1	

PLUG